

SAFETY DATA SHEET

Revision Date: 06-11-2015 Version 1

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE **COMPANY/UNDERTAKING**

Product identifier

Product Code(s): 21000221-M Product Code(s) (DE): - 75400000 **Product Name RUST VETO 221 D**

Product Registration number

Denmark Norway Sweden

EC#

Pure substance/preparation Contains Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Antirust

Uses advised against Any other purpose.

1.3. Details of the supplier of the safety data sheet

Manufacturer, Importer, Supplier

Houghton plc Houghton S.A.S. Houghton Iberica S.A.

604 Bd Albert Camus, Beacon Road Pol. Ind. Can Salvatella-TorreMateu BP 60041 Trafford Park 08210 Barbera del Valles

Manchester 69652 Villefranche sur saone Barcelona M17 1AF **SPAIN** France

Tel: +(34 93) 718 85 00 Tel: +44 (0)161 874 5000 Tel: (0) 4 74 65 65 00 E-mail: MSDS@uk.houghtonglobal.com Fax. (0) 4 74 60 08 44 Fax: +(34 93) 718 93 00 msds.es@houghtonintl.com

Houghton Deutschland GmbH Ragione Sociale: Houghton Italia S.p.A.

Giselherstr. 57. D-44319. Indirizzo: Via Postiglione, 30

Dortmund 10024 Moncalieri (TO) Deutschland **ITALY**

Tel: +49 (0) 231/9277-0. Telefono: (+39) 011 6475811. Fax: +49 (0)231/9277-120 Fax: (+39) 0116472778.

MSDS@houghtonintl.com ITTN-MSDS@houghtonintl.com

Houghton Polska SP z.o.o Houghton Sverige AB

La Cours Gata 4 UlKapelanka 17 30-347 Krakow 252 31 Helsingborg Poland Sverige +48 122665240

Tel: +46 42 29 55 10 E-mail: info.se@houghtonintl.com info@houghton.com.pl HOUGHTON EUROPE N.V Sivuliike Suomessa

Meerpaal 12 A. NL - 4904.SK Oosterhout.

Email: customerservice.nl@houghtonintl.com

Lautamiehentie 3 02770 ESPOO Puh. 00-8596 395 Fax. 09-8596 396 LY: 1957249-8

Houghton Benelux

Fax: +31 162 458205

Telefoon: +31 162458400

E-mail: info@houghton.fi

21000221-M - RUST VETO 221 D

Revision Date: 06-11-2015

Houghton Danmark A/S Mento AS Houghton Ukraine Ltd Energivej 3 DK-4180 Sorø Ukraine, Kiev 04213 Kontinentalveien Postboks 44 13, Prirechnaya St. 4098 Tananger Phone: +38 (044) 360-10-24 Danmark Tel: +45 45 85 23 00 Norway Fax: +38 (044) 426-27-76

Tel: +47 51 64 86 00 E-mail: houghton@houghton.dk www.Mento.no

Houghton CZ s.r.o. Houghton Romania Houghton Kimya San. A.Ş Bartošova 3 2A, Jiului Street Kosuyolu Mah 602 00 Brno 4th Floor / Room 2 Asma Dall Sok 013219 Bucharest Czech Republic No: 1434718 Kadıköy Phone: +420 542 213 332 Phone: +40 21 667 06 15 İstanbul

Türkiye office@houghton.cz Fax: +40 21 667 09 70 Phone Number: +90 216 325 15 15

1.4. Emergency telephone number

3E Company: (+)1 760 476 3961 (Code 333938)

Austria	Notfall-Telefonnummer +43 (0) 1 406 4343					
Belgium	Telefoonnummer voor +32 (0)70 245 245					
Bulgaria	Телефон за спешни случаи +359 2 9154 409					
Croatia	Telefon za izvanredna stanja +385 1 2348 342					
Czech Republic	Telefonní číslo pro naléhavé situace +420 224 919 293					
Denmark	Ring til Giftlinjen på +45 82 12 12 12					
Estonia	Mürgistusteabekeskuse +372 626 93 90					
Finland	Hätäpuhelinnumero +358 09 471 977					
France	Numéro d'appel d'urgence +33 (0)1 45 42 5959					
Hungary	Díjmentesen hívható zöld szám +36 80 20 11 99					
Ireland	Emergency telephone number +353 01 809 2166					
Latvia	Valsts Toksikoloģijas centra Saindēšanās un zāļu informācijas centrs +371 6704 2473					
Lithuania	Neatidėliotina informacija apsinuodijus +370 5 236 20 52					
Netherlands	Telefoonnummer voor +31 30 274 88 88					
Norway	Nødnummer +47 22 59 13 00					
Poland	112					
Portugal	Número de telefone de emergência +351 808 250 143					
Romania	Număr de telefon care poate fi apelat în caz de urgență +021 318 36 06 (08:00-15:00)					
Slovakia	Národné toxikologické informačné centrum +421 2 5477 4166					
Spain	Número de teléfono de emergencia +34 91 562 0420					
Sweden	Telefonnummer för nödsituationer +46 08 33 12 31 (09:00-17:00)					
Switzerland	145; 041 44 251 51 51 (www.toxi.ch)					
Turkey	(+)1 760 476 3959 (Code 333938)					

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aspiration toxicity	Category 1 - (H304)
---------------------	---------------------

2.2. Label Elements

Contains Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C)



Signal Word DANGER

Hazard Statements

H304 - May be fatal if swallowed and enters airways

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements - EU (§28, 1272/2008)

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P331 - Do NOT induce vomiting

P405 - Store locked up

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

No information available

- 0 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
- 4.16 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
- 5.96 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
- 5.96 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
- 5.96 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances / 3.2. Mixtures

This product is a mixture. Health hazard information is based on its ingredients

Chemical Name	EC-No	CAS-No	Weight %	Classification (Reg. 1272/2008)	REACH Registration Number
Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C)	-	-	50% - 100%	Asp. Tox. 1 (H304) (EUH066)	-
Highly refined base oil (Viscosity >20.5 cSt @40°C)	-	-	10% - 25%	**	-
Calcium Sulfonate	-	NOT AVAILABLE	1% - 2.5%	Eye Irrit. 2 (H319)	no data available
2-(2-Butoxyethoxy)ethanol	203-961-6	112-34-5	0% - 1%	Eye Irrit. 2 (H319)	01-2119475104-44-xxx x

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346 See Section 15 for additional information on base oils.

Full text of H- and EUH-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first-aid measures

^{**} Substances for which there are Community workplace exposure limits

General advice Immediate medical attention is required. Do not get in eyes, on skin, or on clothing.

Inhalation Move to fresh air. Potential for aspiration if swallowed. Get medical attention immediately if

symptoms occur.

Skin contact Wash off immediately with soap and plenty of water. Remove and wash contaminated

clothing before re-use.

Eye contact Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while

rinsing.

IngestionDo not induce vomiting without medical advice. Clean mouth with water and afterwards

drink plenty of water. Aspiration hazard if swallowed - can enter lungs and cause damage. If

Revision Date: 06-11-2015

symptoms persist, call a physician.

4.2. Most important symptoms and effects, both acute and delayed

Main Symptoms May be fatal if swallowed and enters airways

4.3. Indication of immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

SECTION 5: FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment:, Use CO2, dry chemical, or foam, Water spray or fog, Cool containers / tanks with water spray

Extinguishing media which shall not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire

5.2. Special hazards arising from the substance or mixture

Special Hazard

In the event of fire and/or explosion do not breathe fumes. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Combustible material. Risk of ignition. Thermal decomposition can lead to release of irritating gases and vapors. This material creates a fire hazard because it floats on water.

Hazardous Decomposition Products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Special protective equipment for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ensure adequate ventilation. Use personal protective equipment. Avoid contact with skin, eyes and clothing.

Advice for non-emergency Eliminate all ignition sources if safe to do so.

personnel

Advice for emergency responders For personal protection see section 8.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

6.3. Methods and materials for containment and cleaning up

After cleaning, flush away traces with water.

6.4. Reference to other sections

See Section 8/12/13 for additional information

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Remove all sources of ignition. Keep away from open flames, hot surfaces and sources of ignition.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep out of the reach of children.

Recommended Shelf Life

No information available.

Incompatible Materials

Strong oxidizing agents, Strong acids, Strong bases

7.3. Specific end uses

Specific use(s) Antirust

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Chemical Name	European Union	United Kingdom	France	Spain
Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C)				VLA-EC: 10 mg/m³ VLA-ED: 5 mg/m³
Highly refined base oil (Viscosity >20.5 cSt @40°C)				VLA-EC: 10 mg/m ³ VLA-ED: 5 mg/m ³
2-(2-Butoxyethoxy)ethanol	TWA: 10 ppm TWA: 67.5 mg/m ³	STEL: 15 ppm STEL: 101.2 mg/m³ TWA: 10 ppm TWA: 67.5 mg/m³	VME: 10 ppm VME: 67.5 mg/m³ VLCT: 15 ppm VLCT: 101.2 mg/m³	STEL: 15 ppm STEL: 101.2 mg/m³ TWA: 10 ppm TWA: 67.5 mg/m³

Chemical Name	Germany	Italy	Portugal	The Netherlands
2-(2-Butoxyethoxy)ethanol	MAK: 10 ppm MAK: 67	TWA: 10 ppm TWA: 67.5		Skin
	mg/m³	mg/m³		STEL: 100 mg/m ³
	Ceiling / Peak: 15 ppm	STEL: 15 ppm STEL: 101.2		TWA: 50 mg/m ³

Ceiling / Peak: 100.5 mg/m³	mg/m³	

Chemical Name	Austria	Switzerland	Poland	Ireland
Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C)				STEL: 10 mg/m ³ TWA: 5 mg/m ³ (Mist)
Highly refined base oil (Viscosity >20.5 cSt @40°C)				STEL: 10 mg/m ³ TWA: 5 mg/m ³ (Mist)
2-(2-Butoxyethoxy)ethanol	STEL 15 ppm STEL 101.2 mg/m ³ MAK: 10 ppm MAK: 67.5 mg/m ³	STEL: 15 ppm STEL: 101.2 mg/m³ MAK: 10 ppm MAK: 67 mg/m³	NDSCh: 100 mg/m³ NDS: 67 mg/m³	TWA: 10 ppm TWA: 67.5 mg/m³ STEL: 15 ppm STEL: 101.2 mg/m³

Chemical Name	Finland	Denmark	Norway	Sweden
Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C)	TWA: 5mg/m³ (Öljysumu)	TWA: 1 mg/m³ (Olietåge)	TWA: 1 mg/m³ (Oljetåke)	LLV: 1 mg/m³ STV: 3 mg/m³ (Oljedimma)
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5mg/m³ (Öljysumu)	TWA: 1 mg/m³ (Olietåge)	TWA: 1 mg/m³ (Oljetåke)	LLV: 1 mg/m³ STV: 3 mg/m³ (Oljedimma)
2-(2-Butoxyethoxy)ethanol	TWA: 10 ppm TWA: 68 mg/m³	TWA: 10 ppm TWA: 68 mg/m³	TWA: 10 ppm TWA: 68 mg/m³ STEL: 20 ppm STEL: 102 mg/m³	LLV: 15 ppm LLV: 100 mg/m³ STV: 30 ppm STV: 200 mg/m³

Chemical Name	Czech Republic	Hungary Bulgaria		Romania
2-(2-Butoxyethoxy)ethanol	Ceiling: 100 mg/m ³	STEL: 101.2 mg/m ³		TWA: 150 mg/m ³
	TWA: 100 mg/m ³	TWA: 67.5 mg/m ³		STEL: 250 mg/m ³

Hydrocarbon solvent vapor mixtures which do not have substance specific occupational exposure limits may be evaluated by the Reciprocal Calculation Procedure (RCP) which assigns a recommended occupational exposure limit based on the mass composition and hydrocarbon group guidance values (GGVs). Applicable recommended occupational exposure limits are shown in the table below.

Chemical Name	RCP OEL	Manufacturer
Distillates (petroleum), hydrotreated middle 64742-46-7	RCP: TWA 1200 mg/m ³ 143ppm	
Distillates (petroleum), hydrotreated light 64742-47-8	RCP: TWA 1200 mg/m ³ 182ppm	
Naphtha (petroleum), hydrotreated heavy 64742-48-9	RCP: TWA 1000 mg/m ³	
C12-C14 isoalkanes 68551-19-9	RCP: TWA 1200 mg/m ³	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	RCP C9-C15 aliphatics: 600mg/m ³	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	TWA: 600 mg/m³	
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, <0.03% aromatics NOT AVAILABLE	RCP C9-C15 aliphatics: 600mg/m ³	
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	TWA: 150ppm TWA: 1200 mg/m³	
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics NOT AVAILABLE	TWA: 171 ppm TWA: 1200 mg/m³	
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics NOT AVAILABLE	RCP C9-C15 aliphatics: 600mg/m ³	
Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	TWA: 165 ppm TWA: 1200 mg/m³	
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2%	RCP: TWA 1200 mg/m ³ 182ppm	

21000221-M - RUST VETO 221 D

aromatics NOT AVAILABLE		
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics NOT AVAILABLE	RCP: TWA 600 mg/m ³	
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	RCP: TWA 600 mg/m ³	

Workers Systemic toxicity

Chemical Name	Long term - Oral exposure	Long term - Dermal exposure	Long term - Inhalation exposure	Short term - Oral Exposure	Short term - Dermal exposure	Short term - Inhalation exposure
2-(2-Butoxyethoxy)ethanol		20 mg/kg	67.5 mg/m ³			

Workers Local effects

Chemical Name	Long term - Oral exposure	Long term - Dermal exposure		Short term - Oral Exposure	Short term - Dermal exposure	
			exposure			exposure
2-(2-Butoxyethoxy)ethanol			67.5 mg/m ³			

Consumers Systemic toxicity

Chemical Name	Long term - Oral exposure	Long term - Dermal exposure	Long term - Inhalation	Short term - Oral Exposure	Short term - Dermal exposure	Short term - Inhalation
			exposure			exposure
2-(2-Butoxyethoxy)ethanol		10 mg/kg	34 mg/m ³			

Consumers Local effects

Chemical Name	Long term - Oral exposure	Long term - Dermal exposure	Long term - Inhalation exposure	Short term - Oral Exposure	Short term - Dermal exposure	Short term - Inhalation exposure
2-(2-Butoxyethoxy)ethanol						50.6 mg/m ³

Predicted No Effect Concentration (PNEC)

Chemical Name	Fresh water	Sea water	Fresh water sediment	Sea sediment	Soil
2-(2-Butoxyethoxy)ethanol	1 mg/L	0.1 mg/L	4 mg/kg	0.4 mg/kg	0.4 mg/kg

8.2. Exposure controls

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye Protection
Hand Protection

Safety glasses with side-shields.

Protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Barrier creams may help to protect the exposed areas of skin, they should

however not be applied once exposure has occurred.

Skin and body protection Respiratory protection

Long sleeved clothing.

No special protective equipment required. In case of mist, spray or aerosol exposure wear

suitable personal respiratory protection and protective suit.

Hygiene measures Do not eat, drink or smoke when using this product. Handle in accordance with good

industrial hygiene and safety practice.

Environmental Exposure Controls

Thermal hazards

No special environmental precautions required.

None under normal use conditions

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state @20°CliquidAppearanceclear , brownOdormineral oilOdor ThresholdNot Applicable

Property Values Note

pH No information available
Melting Point / Freezing Point
Boiling point/boiling range No information available
No information available

Flash point 67 °C / 153 °F ASTM D 93

Evaporation rate

Flammability (solid, gas)

Flammability in Air

Flammability Limits in Air

upper flammability limitNo information availableLower flammability limitNo information available

Vapor pressureNo information availableVapor densityNo information available

Relative density 0.8300 g/cm3 @15°C

Solubility(ies) Insoluble in water Partition coefficient: n-octanol/water Not Applicable

Autoignition temperature No information available No information available

Viscosity, kinematic 2.7 cSt @ 40 °C ASTM D 445

Explosive properties Not Applicable
Oxidizing Properties Not Applicable

9.2 Other information

Viscosity, kinematic (100°C)

Pour point

VOC Content (ASTM E-1868-10)

VOC Content

No information available
No information available
No information available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None under normal use conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None under normal use conditions

10.4. Conditions to avoid

Heat, flames and sparks, Keep away from open flames, hot surfaces and sources of ignition, Heat (temperatures above flash point), sparks, ignition points, flames, static electricity

10.5. Incompatible Materials

Strong oxidizing agents, Strong acids, Strong bases

10.6. <u>Hazardous decomposition products</u>

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Product Information - Principle Routes of Exposure

Inhalation Risk of serious damage to the lungs (by aspiration)

Eye contact None known
Skin contact None known

Ingestion Risk of product entering the lungs on vomiting after ingestion

Acute toxicity - Product Information

May be harmful if swallowed and enters airways.

Acute toxicity - Component Information

Non-hazardous ingredients

Chemical Name	LD50 Oral (Rat)	LD50 Dermal (Rat/Rabbit)	LC50 Inhalation
Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	
Highly refined base oil (Viscosity >20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	
Calcium Sulfonate	>5000 mg/kg (Rat)	>2000 mg/kg (Rabbit)	
2-(2-Butoxyethoxy)ethanol	3384 mg/kg (Rat)	= 2700 mg/kg (Rabbit)	

Skin corrosion/irritation None known.

Serious eye damage/eye irritation None known.

Sensitization

Respiratory Sensitization None known.
Skin sensitization None known.

Germ Cell Mutagenicity None known.

Carcinogenicity None known.

Reproductive toxicity None known.

Specific target organ systemic toxicity (single exposure)

None known

Specific target organ systemic toxicity (repeated exposure)

None known

Aspiration hazard Risk of serious damage to the lungs (by aspiration).

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

No special environmental measures are necessary

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
Calcium Sulfonate		>10000: 96 h Cyprinodon variegatus mg/L LC50		
2-(2-Butoxyethoxy)ethanol	100: 96 h Desmodesmus subspicatus mg/L EC50	1300: 96 h Lepomis macrochirus mg/L LC50 static		2850: 24 h Daphnia magna mg/L EC50 100: 48 h Daphnia magna mg/L EC50

12.2. Persistence and degradability

The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.

12.3. Bioaccumulative potential

No information available

12.4. Mobility in soil

The product is insoluble and floats on water

12.5. Results of PBT and vPvB assessment

This preparation contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This preparation contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

12.6. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused

Products

Dispose of in accordance with local regulations

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal. Observe all label precautions until container is cleaned, reconditioned or

destroyed.

Other Data According to the European Waste Catalogue, Waste Codes are not product specific, but

application specific. Waste codes should be assigned by the user based on the application

for which the product was used.

SECTION 14: TRANSPORT INFORMATION

14.1. UN-Number

Not regulated

14.2. UN proper shipping name

Not regulated

14.3. Transport hazard class

Not regulated

14.4. Packing group

Not regulated

14.5. Environmental Hazards

None

14.6. Special precautions for users

None

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

IMDG/IMONot regulatedADR/RIDNot regulatedICAO/IATANot regulated

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Classification, Labeling and Packaging of Substances and Mixtures (CLP) Regulation (EC 1272/2008) Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

Statutory Instruments: Control of Substances Hazardous to Health Regulations 2002. Chemicals (Hazard Information and Packaging) Regulations 2009.

Acts of Parliament: The Health and Safety at Work etc. Act 1974. Environment Protection Act 1990.

Regulation on classification, labeling. of hazardous chemicals (2002 changing 2005). Appendix VI to Regulation on classification, labeling etc. of hazardous chemicals (2002 changing 2010), list of hazardous substances (as amended). Guidelines for submission and declaration of hazardous waste (2009). Transport of dangerous goods: ADR, RID, IMDG and IATA. Administrative norms for pollution of the atmosphere, 2009.

Workplace exposure limits (EH40)

WGK Classification

Low hazard to water/Class 1

The highly refined base oil (Viscosity >20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical Name	CAS-No	EC-No	REACH Registration Number
Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated	101316-72-7	309-877-7	01-2119489969-06-xxxx
Lubricating oils (petroleum), used, noncatalytically refined	101316-73-8	309-878-2	02-2119822310-56-xxxx
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8	
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6	01-2119488707-21-xxxx
Extracts (petroleum), residual oil solvent	64742-10-5	265-110-5	01-2119488175-30-xxxx
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	01-2119467170-45-xxxx
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6	
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1	01-2119484627-25-xxxx
Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8	01-2119489287-22-xxxx
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3	
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0	01-2119480472-38-xxxx
Distillates (petroleum), solvent-dewaxed heavy, paraffinic	64742-65-0	265-169-7	01-2119471299-27-xxxx
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7	265-174-4	01-2119487080-42-xxxx
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	276-737-9	01-2119474878-16-xxxx
Lubricating oils (petroleum), C20-C50, hydrotreated	72623-87-1	276-738-4	01-2119474889-13-xxxx

neutral oil-based			
Lubricating oils	74869-22-0	278-012-2	
Paraffin oils	8012-95-1	232-384-2	
White mineral oil (petroleum)	8042-47-5	232-455-8	01-2119487078-27-xxxx

The highly refined, low viscosity base oil (Viscosity <7 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical Name	CAS-No	EC-No	REACH Registration Number
Distillates (petroleum), hydrotreated middle	64742-46-7	934-956-3	01-2119827000-58-xxxx
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	64742-46-7	932-078-5	01-2119552497-29-xxxx
Distillates (petroleum), hydrotreated light	64742-47-8	265-149-8	01-2119456620-43-xxxx
Naphtha (petroleum), hydrotreated heavy	64742-48-9	265-150-3	01-2119457273-39-xxxx
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6	01-2119480375-34-xxxx
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7	01-2119487077-29-xxxx
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2	01-2119480132-48-xxxx
C12-C14 isoalkanes	68551-19-9	271-369-5	
White mineral oil (petroleum)	8042-47-5	232-455-8	01-2119487078-27-xxxx
C18-C50 branched, cyclic and linear hydrocarbons – Distillates	848301-69-9	482-220-0	01-0000020163-82-xxxx
Alkanes, C14-16	90622-46-1	292-448-0	
Alkanes, C12-26-branched and linear	90622-53-0	292-454-3	
Alkanes, C11-15-iso-	90622-58-5	292-460-6	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE	926-141-6	01-2119456620-43-xxxx
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE	918-481-9	01-2119457273-39-xxxx
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, <0.03% aromatics	NOT AVAILABLE	934-954-2	01-2119826592-36-xxxx
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE	920-107-4	01-2119453414-43-xxxx
Hydrocarbons, C11-C14, n-alkanes, <2% aromatics	NOT AVAILABLE	924-803-9	01-2119485647-22-xxxx
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	NOT AVAILABLE	920-901-0	01-2119456810-40-xxxx
Hydrocarbons, C14-C18, n-alkanes, cyclics, aromatics (2-30%)	NOT AVAILABLE	920-360-0	01-2119448343-41-xxxx
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	NOT AVAILABLE	918-167-1	01-2119472146-39-xxxx
Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE	927-285-2	01-2119480162-45-xxxx
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE	927-676-8	01-2119456377-30-xxxx
Hydrocarbons, C13-C16, isoalkanes, cyclics, < 2% aromatics	NOT AVAILABLE	918-973-3	01-2119458871-30-xxxx
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics	NOT AVAILABLE	934-956-3	01-2119827000-58-xxxx
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE	927-632-8	01-2119457736-27-xxxx

15.2. Chemical Safety Assessment

No information available

SECTION 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Repr.-Reproduction toxicity Asp. Tox. - Aspiration Toxicity Acute Tox. - Acute Toxicity

Aquatic Acute - Acute Aquatic Toxicity
Aquatic Chronic - Chronic Aquatic Toxicity

Eye Dam. - Eye Damage

21000221-M - RUST VETO 221 D

Eye Irrit. - Eye Irritation Skin Corr. - Skin Corrosion Skin Irrit. - Skin Irritation Skin Sens. - Skin Sensitizer

Resp. Sens. - Respiratory Sensitizer

STOT SE - Specific target organ systemic toxicity (Single exposure) STOT RE - Specific target organ systemic toxicity (repeated exposure)

VOC - Volatile organic compounds

Full text of H-Statements referred to under sections 2 and 3

H224 - Extremely flammable liquid and vapor	H341 - Suspected of causing genetic defects
 H225 - Highly flammable liquid and vapor 	H350 - May cause cancer
H226 - Flammable liquid and vapor	H351 - Suspected of causing cancer
 H270 - May cause or intensify fire; oxidizer 	H360 - May damage fertility or the unborn child
 H271 - May cause fire or explosion; strong oxidizer 	H361 - Suspected of damaging fertility or the unborn child
H272 - May intensify fire; oxidizer	H362 - May cause harm to breast-fed children
H290 - May be corrosive to metals	H370 - Causes damage to organs
H300 - Fatal if swallowed	H371 - May cause damage to organs
H301 - Toxic if swallowed	H372 - Causes damage to organs through prolonged or repeated
H302 - Harmful if swallowed	exposure
H304 - May be fatal if swallowed and enters airways	H373 - May cause damage to organs through prolonged or repeated
H310 - Fatal in contact with skin	exposure
H311 - Toxic in contact with skin	H400 - Very toxic to aquatic life
H312 - Harmful in contact with skin	H410 - Very toxic to aquatic life with long lasting effects
 H314 - Causes severe skin burns and eye damage 	H411 - Toxic to aquatic life with long lasting effects
H315 - Causes skin irritation	H412 - Harmful to aquatic life with long lasting effects
H317 - May cause an allergic skin reaction	H413 - May cause long lasting harmful effects to aquatic life
H318 - Causes serious eye damage	H360Df - May damage the unborn child. Suspected of damaging fertility
H319 - Causes serious eye irritation	H360D - May damage the unborn child
H330 - Fatal if inhaled	H360FD - May damage fertility. May damage the unborn child
H331 - Toxic if inhaled	H360F - May damage fertility
H332 - Harmful if inhaled	H361d - Suspected of damaging the unborn child
 H334 - May cause allergy or asthma symptoms or breathing difficulties 	es H361fd - Suspected of damaging fertility. Suspected of damaging the
if inhaled	unborn child
H335 - May cause respiratory irritation	H361f - Suspected of damaging fertility
H336 - May cause drowsiness or dizziness	EUH066 - Repeated exposure may cause skin dryness or cracking
H340 - May cause genetic defects	EUH210 - Safety data sheet available on request
	EUH208 - May produce an allergic reaction

Exposure scenario

No information available

Revision Date: 06-11-2015

Revision Note

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.